

Navgrun



Nithin Sai Renewables Pvt Ltd

 www.navgrun.com

 info@navgrun.com




MBB Mono PERC P-Type M10 Halfcut-cell

NS500M, 525 - 550/1500 V Series

Bi-Facial Transparent Back Sheet

Navgrun



POWER



Module power from **525 W to 550 W**



Comprehensive LID/Le TID mitigation technology, up to 50% lower degradation



Cost effective product for utility power plant



Less shading effect

RELIABILITY



Heavy snow load up to 5400 Pa
Heavy load up to 2400 Pa



Low temperature coefficient



**LINEAR PERFORMANCE
WARRANTY**



PRODUCT WARRANTY

ALMM & BIS Approved

Advanced Technology Features



Cylindrical

Tabbing Wire reduces the shadow on active cells and increases the PV module's generation efficiency.



Higher Power Output

Enhanced module output 5-25% generally, bringing significantly lower LCOE and higher IRR.



Field Reliability

Improved due to multi-contacts in the cell, reducing cell stress.



Minimal Power Loss

Optimized through low Internal Resistance.



Industry Leading

30 years linear performance warranty.



PID Resistance

Excellent Anti-PID performance guarantee via optimised mass-production process and materials control.



Bypass Diodes

Within split JB enable PV module to perform in partial shadow conditions.



Strong Quality

Check and Quality Assurance with Pre and Post EL tests.

Certifications

IEC 61215 2021, 61730 1-2 2016, 61701 (Sev 6 ed. 3), 62716	BIS Certified
IEC 60068	CE Certified
IEC TS 62804	LeTID
IEC 61853-1 & 2	UL 61730 2017



TECHNICAL DATA

MBB Mono PERC M10 Halfcut-cell

NS500M 525- 550/1500 V Series | Bi-Facial Transparent Backsheet

Navgrun

Electrical Parameters at STC

Model	NS-P10-144HT-500 Series						
Module Type	UoM	NS-P10-144HG 525	NS-P10-144HG 530	NS-P10-144HG 535	NS-P10-144HG 540	NS-P10-144HG 545	NS-P10-144HG 550
Maximum Power (Pmax)	Wp	525	530	535	540	545	550
Maximum Voltage (Vmpp)	V	41.29	41.45	41.60	41.75	41.86	41.90
Maximum Current (Impp)	A	12.73	12.80	12.88	12.95	13.04	13.14
Open Circuit Voltage (Voc)	V	49.16	49.31	49.46	49.61	49.65	49.70
Short Circuit Current (Isc)	A	13.63	13.69	13.76	13.83	13.80	13.82
Module Efficiency	%	20.33	20.53	20.72	20.91	21.11	21.30

STC: Irradiance 1000 W/m², module temperature 25°C, air mass 1.5 g, spectrum according to EN 60904-3.
Power measurement tolerance is -0 ~± 5Wp. Voc and Isc tolerance ±3%.
Maximum system voltage 1500 V, Maximum Fuse Rating 25A.

Electrical Parameters at NOCT

Model	NS-P10-144HT-500 Series						
Module Type	UoM	NS-P10-144HG 525	NS-P10-144HG 530	NS-P10-144HG 535	NS-P10-144HG 540	NS-P10-144HG 545	NS-P10-144HG 550
Maximum Power (Pmax)	Wp	390	390	394	397	401	405
Maximum Voltage (Vmpp)	V	38.79	38.82	38.86	38.90	38.94	38.98
Maximum Current (Impp)	A	9.96	10.04	10.13	10.21	10.30	10.39
Open Circuit Voltage (Voc)	V	46.05	46.08	46.12	46.16	46.19	46.53
Short Circuit Current (Isc)	A	10.66	10.75	10.85	10.94	11.03	11.14
Module Efficiency	%	14.94	15.09	15.23	15.37	15.51	15.62

NOCT: Irradiance 800 W/m², ambient temperature 20°C, wind speed 1m/s, tolerance ±3%.

Mechanical Data

Length x Width x Height	2278 x 1134 x 35 mm, ± 2 mm
Weight	28 kg
Junction Box	IP68, 3 Split Junction Box with Individual Bypass Diodes
Output Cable	Length: 400 mm / As Per Customer Requirement, Dia: 4 mm ²
Connector	MC4 Compatible
Application Class	Class A (Safety Class II)
Glass Front/Rear	High Transmittance ARC Glass, 3.2 mm/ Transparent Back Sheet
Solar PV Cells	72 Mono PERC (144 Halfcut-Cells) P Type
Cell Encapsulant	EVA (Ethylene Vinyl Acetate)
Frame	Anodised (15 µ) Aluminium Frame, Silver
Mechanical Load Test	5400 Pa (Snow Load), 2400 Pa (Wind Load)
Fire Performance	Type 4 (UL 61730) or Class C (IEC 61730)
Country of Origin	India

Operating Conditions

Temperature Coefficient Voc, β	-0.27%/°C
Temperature Coefficient Isc, α	0.05%/°C
Temperature Coefficient Pmax, γ	-0.30%/°C
NOCT	42°C±2°C
Temperature range	-40°C to +85°C


- 25-Year Linear Power Output Warranty
- 12-Year Product Warranty

- <2.0% degradation for 1st year
- 0.45% from 2nd year onward to 25th year

Note: The specifications in this data sheet may deviate slightly from our actual products due to the ongoing innovation and product enhancement. We reserve the right to make necessary adjustments to the information described herein at any time without further notice.

Typical I-V Curves


Cell Temperature 25°C



Packaging Information

Container	20'GP	32'HQ	40'HQ
Quantity per Pallet	31	31	31
Pallet/Container	8	16	20
Quantity/Container	248	496	620

Mechanical Diagrams



Remark: Customized frame colour and length available upon request

***WARRANTY: Please refer the Warranty Card.**

***CAUTION: Please read safety and installation instructions before using the product.**

Contact Us

Nithin Sai Renewables Pvt Ltd

www.navgrun.com

info@navgrun.com

+91 9606080780

Corporate Office

Balsa N1, 2nd Floor, Embassy Manyata Business Park, Outer Ring Road, Nagavara, Rachenahalli Village, KR Puram Hobli, Bangalore, India - 560045

Factory

Plot No. 75-A, 2nd Phase, KIADB Industrial Area, Chintamani Taluk, Mastenahalli Industrial Area, Chikkaballapur, Karnataka - 563128